

SAFETY DATA SHEET according to 1907/2006/EC, Article 31

<u>1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE</u> <u>COMPANY/UNDERTAKING</u>

Product details Trade name: Fiberglass Light Putty Article number: 15334, 15335 Intended use: Car refinishing Product/ Knife filler/ Surfacer Manufacturer/Supplier: Chamäleon GmbH Rudolf-Diesel-Straße, 8a, 69155 Heidelberg -- Germany Further information obtainable from: Product Safety Department Information in case of emergency: + 49 70024112112 (CH)

2 – HAZARDS IDENTIFICATION

Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC Xn; Harmful

R48: Danger of serious damage to health by prolonged exposure.

R10: Flammable.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.



Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. **Hazard pictograms**



GHS02 GHS07 GHS08 Signal word Danger Hazard-determining components of labelling: Styrol Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H372 Causes damage to organs through prolonged or repeated exposure. **Precautionary statements** P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P260 Do not breathe vapours. P280 Wear protective gloves/protective clothing/eye protection/face protection.

- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P501 Dispose of contents / container in accordance with regional regulations.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

<u>3– COMPOSITION/INFORMATION ON INGREDIENTS</u>

Chemical characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:			
CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.:01-2119491274-35	barium sulphate, natural substance with a Community workplace exposure limit	12.5-<20%	
CAS: 100-42-5	Styrol Xn R20-48-65; Xi R36/37/38 R10	12.5-<20%	
	Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox.4, H332; Skin Irrit.2, H315; Eye Irrit 2, H319; STOT SE 3, H335		



Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply. For the wording of the listed risk phrases refer to section 16.

<u>4– FIRST - AID MEASURE</u>

Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

<u>5– FIRE - FIGHTING MEASURE</u>

Extinguishing media
Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
For safety reasons unsuitable extinguishing agents:
Water
Water with full jet
Special hazards arising from the substance or mixture No further relevant information available.
Advice for firefighters -

6- ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: No special measures required.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.



7- HANDLING AND STORAGE

Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: Not required.
Further information about storage conditions: Keep container tightly sealed.
Storage class: 10
Specific end use(s) No further relevant information available.

<u>8 – EXPOSURE CONTROLS / PERSONAL PROTECTION</u>

Additional information about design of technical facilities: No further data; see item 7. Control parameters

Ingredients with limit values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

WEL	Long-term value: 10* 4** mg/ m ³
	*inhalable dust **respirable dust

Additional information: The lists valid during the making were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection: Not required.

Protection of hands:

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl shoud be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves Butyl rubber, BR

Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Eye protection: Safety glasses

Chamäleon GmbH- Safety Data Sheet



9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chem	nical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	145°C
Flash point:	31°C
Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of
	explosive air/ vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
Vapour pressure at 20°C:	6 hPa
Density at 20°C:	$1.1 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/ water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
VOC- (EU)	
	4.2 g/l
Other information	No further relevant information available.

10-STABILITY AND REACTIVITY

Reactivity Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.



Possibility of hazardous reactions No dangerous reactions known. **Conditions to avoid** No further relevant information available. **Incompatible materials:** No further relevant information available. **Hazardous decomposition products:** No dangerous decomposition products known.

<u>11– TOXILOGICAL INFORMATION</u>

Information on toxicological effects Acute toxicity: Primary irritant effect: on the skin: No irritant effect. on the eye: No irritating effect. Sensitization: No sensitizing effects known. Additional toxicological information: The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Vapours have narcotic effect.

<u> 12 – ECOLOGICAL INFORMATION</u>

Toxicity

Aquatic toxicity: No further relevant information available. Persistence and degradability No further relevant information available. Bioaccumulative potential No further relevant information available. Mobility in soil No further relevant information available. Additional ecological information: General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

<u> 13– DISPOSAL CONSIDERATION</u>

Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.



European waste catalogue		
08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous	
	substances	
15 01 04	metallic packaging	

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14-TRANSPORT INFORMATION

UN-Number ADR, IMDG, IATA

UN 3269

UN proper shipping name ADR IMDG, IATA

UN3269 POLYESTER RESIN KIT POLYESTER RESIN KIT

Transport hazard class(es) ADR



Class Label 3 (FT3) Flammable liquids.

3 Flammable liquids.

IMDG, I ATA



Class Label

Packing group ADR, IMDG, I AT A

III

3

Environmental hazards: Marine pollutant:

No

Special precautions for userWarning: Flammable liquids.Danger code (Kemler):30EMS Number:F-E,S-D

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.



Transport/Additional information: ADR Limited quantities (LQ) Transport category Tunnel restriction code

5L 3 E

UN "Model Regulation": UN3269, POLYESTER RESIN KIT, 3, III

<u>15 – REGULATORY INFORMATION</u>

Safety, health and environmental regulations/legislation specific for the substance or mixture .

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

<u>16-OTHER INFORMATION</u>

Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H372 Causes damage to organs through prolonged or repeated exposure.
- R10 Flammable.
- R20 Harmful by inhalation.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R48 Danger of serious damage to health by prolonged exposure.
- R65 Harmfull: may cause lung damage if swallowed

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.