



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
<http://www.chamaeleon/produktion.de>

TECHNICAL DATA SHEET

CHAMÄLEON PRE-FILL

Article number: 25001

Intended use: Car refinishing Product/ Preparation

General characteristics:

Chamäleon pre-fill standard is a pre-filled can with propellant gases and solvent that can be filled with solvent-based basecoats. Ideal for spot repairs or refinishing parts.

Product characteristics:

- A spray can pre-filled with propellant and solvents. The paint is transferred via a filling device into the can to produce a ready-to-use end product (dealers liability)
- Simple, time-saving application
- Excellent atomisation
- Light blending

Physical and Chemical Characteristics:

Colour: depending on filling

Smell: solvent

Efficiency: Depending on consistence and colour of the ground

Substrate: Depending on the colour of the substrate apply Primer Filler, 2K Primer Filler, 1K Epoxy Primer, cured paint sanded

Drying time (at 20°C, 50% relative air humidity): The drying time depends on surrounding temperature, air humidity, thickness of the applied coat and the filled type of paint (refer to information of the paint manufacturer)

Storage stability: empty cans: 5 years. Filled cans: depending on type of paint from several hours up to 6 month (information from your specialist dealer). If appropriate storage provided (=10°-25°C, relative air humidity max. 60%)

Size: Aerosol cans, maximum nominal volume 400 ml.

VOC-value: 218g



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
<http://www.chamaeleon/produktion.de>

Usage:

Before use, carefully read the directions on the packaging and act accordingly.

- Clean the surface to be painted thoroughly with Chamaeleon silicone remover, then sand
 - Larger bare surfaces must be pre-primed with the appropriate Chamaeleon primer
 - The area must be dry and free of dust and grease
 - Shake the can vigorously for 2 minutes
 - Carry our spray test
 - Compatibility testing is necessary
-
- **For professional use only**
 - **Wear an appropriate respirator (recommended type A2/P3)**

Environment and labelling

Environmentally sound: The products are 100% free of heavy metals.
The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

*For the additional information that is not included to the Technical Data Sheet apply to the supplier:
e-mail: info@chamaeleon-produktion.de
See information on safety in Safety Data Sheet.*