

Chamäleon GmbH Rudolf-Diesel-Straße, 8a 69115 Heidelberg-Germany Tel.: +49-(0)-6221 520440 Fax: +49-(0)-6221 520449 E-mail: info@chamaeleon/produktion.de http://www.chamaeleon/produktion.de

TECHNICAL DATA SHEET

CHAMÄLEON THICK LAYER FILLER

Article number:

26040

Intended use:

Car refinishing Product/ Preparation

General characteristics:

Chamäleon thick layer filler is advanced filler with excellent filling properties and coverage. It is highly suitable for levelling superficial scratches and minor irregularities in sanded surfaces. It offers excellent adhesion on polyester filler, plastics and metal. It has a very good flow, is wet-on-wet re-sprayable and easy to sand.

Product characteristics:

- Advanced 1K filler with excellent filling properties and coverage
- Wet-on-wet application possible
- Good adhesion to all metal surfaces
- Very smooth flow

Physical and Chemical Characteristics:

Basis of binder: NC-Acrylic resin
Colour: grey
Smell: solvent
Efficiency: 400ml are sufficient for approx. 1,25 - 1,75 m²
Substrate: blank metall, sanded, sanded, priming of spare parts, sanded, cured paintings, sanded, polyester substrates, sanded
Temperature resistance: to110°C
Storage stability: 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)



Chamäleon GmbH Rudolf-Diesel-Straße, 8a 69115 Heidelberg-Germany Tel.: +49-(0)-6221 520440 Fax: +49-(0)-6221 520449 E-mail: info@chamaeleon/produktion.de http://www.chamaeleon/produktion.de

Usage:

Before use, carefully read the directions on the packaging and act accordingly.

- Remove all rust from damaged areas, where appropriate
- Clean surface thoroughly and sand
- Damaged area must be dry and free of grease and dust
- Shake the can well for 2 minutes
- Carry our spray test
- Clean undercoat with Silicone Remover
- Do not overcoat with polyester products

Environment and labelling

Environmentally sound: The products are 100% free of heavy metals.

The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: <u>info@chamaeleon-produktion.de</u>



Chamäleon GmbH Rudolf-Diesel-Straße, 8a 69115 Heidelberg-Germany Tel.: +49-(0)-6221 520440 Fax: +49-(0)-6221 520449 E-mail: info@chamaeleon/produktion.de http: //www. chamaeleon/produktion.de

See information on safety in Safety Data Sheet.