



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
<http://www.chamaeleon/produktion.de>

TECHNICAL DATA SHEET

CONTROL GUIDE COAT BLACK

Article number:	26051
Intended use:	Car refinishing Product/ Preparation
General characteristics:	High quality black control lacquer as aid for sanding.
Product characteristics:	Easy in use Fast drying

Physical and Chemical Characteristics:

Contents	500 ml
Base	Nitro-cellulose binder
Colour	Black
VOC-content	Approximately 92% w/w
Coverage	3 to 4 ml
Sandable	After 5 to 10 minutes

Usage:

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment: The surface should be clean, dry and free of grease.

Treatment: The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre. Apply a thin layer of sanding aid and allow to dry. Sand the surface till the control lacquer is completely removed. After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

**For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: info@chamaeleon-produktion.de
See information on safety in Safety Data Sheet.**