



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
<http://www.chamaeleon/produktion.de>

TECHNICAL DATA SHEET

CHAMÄLEON ACRYLIC AEROSOL

Article number: 26204 (Black matt), 26214 (Black glossy)
26414 (White glossy) 26404 (Clear coat)

Intended use: Car refinishing Product/ Clear coating material,
Varnish

General characteristics: For the treatment of surfaces, treated and untreated,
of wood, metal, aluminium, glass, stone and
various types of plastic.

Product characteristics:

- Fast drying
- Good coverage
- Lasting gloss
- Non-fading and UV resistant
- Good surface hardness
- Resistant to petrol, chemicals and weather influences
- Wear resistant and scratch free
- Excellent adhesion

Technical characteristics:

Contents: 500 ml
Base: Acrylic resin
Colour: Black
VOC-content: Approximately 91% w/w
Solid Content: Approximately 9% w/w
Coverage: 1,5 to 2 m² Approximately 0,5 m²
Dust dry: After 5 to 10 minutes
Tack free: After 10 to 20 minutes
Hardened/re-sprayable: After 2 hours
Heat resistant: To 110°C



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
<http://www.chamaeleon/produktion.de>

Usage:

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment:

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. Apply a layer of Chamaeleon Spray Primer suitable for the surface. After drying, sand the base layer (grain 600).

Treat:

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

After use:

Clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

For the additional information that is not included to the Technical Data Sheet apply to the supplier:



*e-mail: info@chamaeleon-produktion.de
See information on safety in Safety Data Sheet.*

Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
<http://www.chamaeleon/produktion.de>