



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http: //www.chamaeleon-produktion.de

***SAFETY DATA SHEET***  
***according to 1907/2006/EC, Article 31***

Revision date: 07.12.2017

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**

**Product details**

**Trade name:** Structure Spray

**Article number:** 26340

**Intended use:** Car refinishing Product/Spray varnish

**Relevant identified uses of the substance or mixture and uses advised against:**

No further relevant information available.

**Sector of Use:**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category:** PC9a Coatings and paints, thinners, paint removers

**Process category:**

PROC7 Industrial spraying

PROC11 Non industrial spraying

**Manufacturer/Supplier:** Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg -- Germany

**Further information obtainable from:** Product Safety Department

**Information in case of emergency:** + 49 70024112112 (CH)

**2 – HAZARDS IDENTIFICATION**

**Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

**Label elements**

**Labelling according to Regulation (EC) No 1272/2008:**

The product is classified and labelled according to the CLP regulation.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http://www.chamaeleon-produktion.de

**Hazard pictograms:**



GHS02 GHS07

**Signal word :** Danger

**Hazard-determining components of labelling:**

ethyl acetate

n-butyl acetate

butanone

**Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

**Precautionary statements:**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**3- COMPOSITION/INFORMATION ON INGREDIENTS**

**Chemical characterisation:** Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

<b>Dangerous components:</b>			
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane	Flam. Gas 1, H220 Press. Gas C, H280	12.5-<20



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon-produktion.de  
 http://www.chamaeleon-produktion.de

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate	Flam. Liq. 3, H226 STOT SE 3, H336	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane	Flam. Gas 1, H220 Press. Gas C, H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane	Flam. Gas 1, H220 Press. Gas C, H280	5-<10%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	5-<10%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol	Flam. Liq. 2, H225	<2.5%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### **4- FIRST - AID MEASURE**

##### **Description of first aid measures**

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Generally the product does not irritate the skin.

##### **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

**Most important symptoms and effects, both acute and delayed** No further relevant information available.

##### **Indication of any immediate medical attention and special treatment needed**

No further relevant information available

#### **5- FIRE - FIGHTING MEASURE**

##### **Extinguishing media**

##### **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

**Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

**Advice for firefighters -**

**Protective equipment:** Mouth respiratory protective device.

**6- ACCIDENTAL RELEASE MEASURE**

**Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources.

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

**Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**7- HANDLING AND STORAGE**

**Precautions for safe handling:** Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** Keep container tightly sealed.

**Storage class:** 2 B

**Specific end use(s)** No further relevant information available.



## **8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Additional information about design of technical facilities:** No further data; see item 7.

### **Control parameters**

<b>Ingredients with limit values that require monitoring at the workplace:</b>	
141-78-6 ethyl acetate	
WEL	Short-term value: 400 ppm Long-term value: 200 ppm
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
106-97-8 butane	
WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
78-93-3 butanone	
WEL	Short-term value: 899 mg/m <sup>3</sup> , 300 ppm Long-term value: 600 mg/m <sup>3</sup> , 200 ppm Sk, BMGV
64-17-5 ethanol	
WEL	Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm
<b>Ingredients with biological limit values:</b>	
78-93-3 butanone	
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one

**Additional information:** The lists valid during the making were used as basis.

### **Exposure controls**

#### **Personal protective equipment:**

#### **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.
- Avoid contact with the eyes.

#### **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon-produktion.de  
 http: //www.chamaeleon-produktion.de

**Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**

Tightly sealed goggles

**9 – PHYSICAL AND CHEMICAL PROPERTIES**

<b>Information on basic physical and chemical properties</b>	
<b>General Information</b>	
<b>Appearance:</b>	
<b>Form:</b>	<i>Aerosol</i>
<b>Colour:</b>	<i>Black</i>
<b>Odour:</b>	<i>Solvent-like</i>
<b>Odour threshold:</b>	<i>Not determined.</i>
<b>pH-value:</b>	<i>Not determined.</i>
<b>Change in condition</b>	
<b>Melting point/freezing point:</b>	<i>Undetermined.</i>
<b>Initial boiling point and boiling range:</b>	<i>Not applicable, as aerosol.</i>
<b>Flash point:</b>	<i>&lt;0 °C (&lt;32 °F) Not applicable, as aerosol.</i>
<b>Flammability (solid, gas):</b>	<i>Not applicable.</i>
<b>Ignition temperature:</b>	<i>365 °C (689 °F)</i>
<b>Decomposition temperature:</b>	<i>Not determined.</i>



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon-produktion.de  
 http: //www.chamaeleon-produktion.de

<b>Auto-ignition temperature:</b>	<i>Product is not selfigniting.</i>
<b>Explosive properties:</b>	<i>Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.</i>
<b>Explosion limits:</b>	
<b>Lower:</b>	<i>1.7 Vol %</i>
<b>Upper:</b>	<i>11.5 Vol %</i>
<b>Vapour pressure at 20 °C (68 °F):</b>	<i>3,500 hPa (2.3 mm Hg)</i>
<b>Density at 20 °C (68 °F):</b>	<i>0.79 g/cm<sup>3</sup> (6.59 lbs/gal)</i>
<b>Relative density</b>	<i>Not determined.</i>
<b>Vapour density</b>	<i>Not determined.</i>
<b>Evaporation rate</b>	<i>Not applicable.</i>
<b>Solubility in / Miscibility with water:</b>	<i>Not miscible or difficult to mix.</i>
<b>Partition coefficient: n-octanol/water:</b>	<i>Not determined.</i>
<b>Viscosity:</b>	
<b>Dynamic:</b>	<i>Not determined.</i>
<b>Kinematic:</b>	<i>Not determined.</i>
<b>Solvent content:</b>	
<b>Organic solvents:</b>	<i>80.2 %</i>
<b>EU-VOC:</b>	<i>635.2 g/l</i>
<b>EU-VOC in %:</b>	<i>80.20 %</i>
<b>VOC (EC)</b>	<i>---</i>
	<i>635.2 g/l</i>
<b>VOC-EU%</b>	<i>80.20 %</i>
<b>Solids content:</b>	<i>0.0 %</i>
<b>Other information</b>	<i>No further relevant information available.</i>

## 10- STABILITY AND REACTIVITY

**Reactivity** No further relevant information available.

### **Chemical stability**

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of hazardous reactions** No dangerous reactions known.

**Conditions to avoid** No further relevant information available.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:** No dangerous decomposition products known



## 11- TOXICOLOGICAL INFORMATION

### Information on toxicological effects

**Acute toxicity** Based on available data, the classification criteria are not met.

<b>LD/LC50 values relevant for classification:</b>		
123-86-4 n-butyl acetate		
Oral	LD50	10,800 mg/kg (rat)
Dermal	LD50	>17,600 mg/kg (rabbit)
Inhalative	LC50 / 4h	1.85 mg/l (rat)
78-93-3 butanone		
Oral	LD50	>2,193 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	34 mg/m <sup>3</sup> (rat)
64-17-5 ethanol		
Oral	LD50	10,470 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50 / 4h	120 mg/l (rat)

### Primary irritant effect:

**Skin corrosion/irritation:** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation:** Causes serious eye irritation

**Respiratory or skin sensitization:** Based on available data, the classification criteria are not met.

### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

**Carcinogenicity:** Based on available data, the classification criteria are not met.

**Reproductive toxicity:** Based on available data, the classification criteria are not met.

**STOT-single exposure:** May cause drowsiness or dizziness.

**STOT-repeated exposure:** Based on available data, the classification criteria are not met.

**Aspiration hazard:** Based on available data, the classification criteria are not met.

## 12 – ECOLOGICAL INFORMATION

### Toxicity

<b>Aquatic toxicity:</b>	
123-86-4 n-butyl acetate	
LC50 / 96 h	81 mg/l (fish)
78-93-3 butanone	
LC50 / 48 h	308 mg/l (daphnia magna)
LC50 / 72 h	1,972 mg/l (Pseudokirchneriella Subcapitata)
LC50 / 96 h	2,990 mg/l (fish)





Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon-produktion.de  
 http://www.chamaeleon-produktion.de

64-17-5 ethanol	
LC50/96h	13,000 mg/l (oncorhynchusmykiss / Regenbogenforelle)
EC50 / 48 h	12,900 mg/l (algae)
LC50 / 48 h	12,340 mg/l (daphnia magna)

**Persistence and degradability** No further relevant information available.

**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

**Additional ecological information:**

**General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**Other adverse effects** No further relevant information available

**13- DISPOSAL CONSIDERATION**

**Waste treatment methods**

**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

<b>European waste catalogue</b>	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 04	metallic packaging

**Uncleaned packaging:**

**Recommendation:** Non contaminated packagings may be recycled.

**14- TRANSPORT INFORMATION**

**UN-Number**

ADR, IMDG, IATA

UN1950

**UN proper shipping name**

ADR

1950 AEROSOLS

IMDG

AEROSOLS

IATA

AEROSOLS, flammable



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon-produktion.de  
 http://www.chamaeleon-produktion.de

**Transport hazard class(es)**

ADR



Class 2 5F Gases.  
 Label 2.1

IMDG, IATA



Class 2.1  
 Label 2.1

**Packing group**

ADR, IMDG, IATA not regulated

**Environmental hazards:**

Not applicable.

**Special precautions for user**

Warning: Gases.

Danger code (Kemler):

-

EMS Number:

F-D,S-U

Stowage Code

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:

Category A. For AEROSOLS with a capacity above 1 litre:

Category B. For WASTE AEROSOLS: Category C, Clear

of living quarters.

Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1

except for division 1.4. For AEROSOLS with a capacity

above 1 litre: Segregation as for the appropriate

subdivision of class 2. For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

**Transport in bulk according to Annex II of  
 Marpol and the IBC Code**

Not applicable.

**Transport/Additional information:**

ADR

Limited quantities (LQ)

1L

Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http: //www.chamaeleon-produktion.de

<b>Transport category</b>	2
<b>Tunnel restriction code</b>	D
<b>IMDG</b>	
<b>Limited quantities (LQ)</b>	1L
<b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity
<b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

### **15 – REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category P3a** FLAMMABLE AEROSOLS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 40

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### **16-OTHER INFORMATION**

#### **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.