



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon/produktion.de](mailto:info@chamaeleon/produktion.de)  
<http://www.chamaeleon/produktion.de>

## TECHNICAL DATA SHEET

### CHAMÄLEON SPOT BLENDER AEROSOL

<b>Article number:</b>	26504
<b>Intended use:</b>	Car refinishing Product/ Preparation
<b>General characteristics:</b>	High quality mixture of solvents to level the transition at spot repairs.
<b>Product characteristics:</b>	<ul style="list-style-type: none"><li>• Directed jetspray</li><li>• Fine spray</li><li>• As a result of the blending of the overspray, a smooth transition is obtained between the old and the new</li><li>• lacquer</li><li>• Instant (in)visible result</li></ul>

#### Physical and Chemical

#### Characteristics

Contents	150 ml
VOC-content	Approximately 99,5 % w/w

#### Usage:

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol.

The Spotblender can be applied when the lacquer is tack free.

Spray the surface with spotblender till the overspray blends like a film.

**The drying time depends on the ambient temperature and the humidity of the air.**

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

*For the additional information that is not included to the Technical Data Sheet apply to the supplier:  
e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
See information on safety in Safety Data Sheet.*



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon/produktion.de](mailto:info@chamaeleon/produktion.de)  
<http://www.chamaeleon/produktion.de>