



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

## **TECHNICAL DATA SHEET**

*Date of issue 24.02.2017*

### **HOLLOW SECTION WAX**

**Article number:** 26740

**Intended use:** Car refinishing Product/ Anticorrosion additive

**Product description:** High quality preservative to treat the hollow spaces in vehicle bodywork.

**Product characteristics:**

- Excellent corrosion prevention
- Excellent adhesion
- Resistant to weather influences
- Resistant to weak acids and bases
- Good penetrating quality

**Physical and Chemical Characteristics:**

Contents : 500 ml  
Colour : White transparent  
VOC-content : Approximately 77% w/w

**Usage:**

**Before use, carefully read the directions on the packaging and act accordingly.**

**Treatment**

The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes.

Apply the wax generously in the hollow areas by means of the adapter.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

**Data: 10, August 2017**

***This release replaces all eventually earlier issued versions.***

***For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)***

***See information on safety in Safety Data Sheet.***