



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon/produktion.de  
http://www.chamaeleon/produktion.de

**SAFETY DATA SHEET**  
*according to 1907/2006/EC, Article 31*

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**

**Product details**

**Trade name:** Bitum Spray

**Article number:** 37100

**Intended use:** Car refinishing Product/ Paint

**Manufacturer/Supplier:** Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69155 Heidelberg -- Germany

**Further information obtainable from:** Product Safety Department

**Information in case of emergency:** + 49 70024112112 (CH)

**2 – HAZARDS IDENTIFICATION**

**Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229      Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2    H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

**Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

F+; Extremely flammable

R12: Extremely flammable.

N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon/produktion.de  
http://www.chamaeleon/produktion.de

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurised container.

Has a narcotising effect.

**Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

**Label elements**

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**



GHS02 GHS07 GHS09

**Signal word** Danger

**Hazard-determining components of labelling:**

Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)

Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)

acetone

Solvent naphtha (petroleum), light arom. (< 0,1 % benzol CAS nr. 71-43-2)

**Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon/produktion.de  
 http://www.chamaeleon/produktion.de

### 3- COMPOSITION/INFORMATION ON INGREDIENTS

#### **Chemical characterization: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-49-0 EC number: 921-024-6 Index number: 649-328-00-1 Reg.nr.: 01-2119475514-35-xxxx	Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2) Xn R65 Xi R38 F R11 N R51/53 R67	12.5-20%
	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane F+ R12	12.5-20%
	Flam. Gas 1, H220 Press. Gas C, H280	
CAS: 64742-49-0 EC number: 920-750-0 Index number: 649-328-00-1 Reg.nr.: 01-2119473851-33-xxxx	Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2) Xn R65 F R11 N R51/53 R66-67	12.5-20%
	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx	acetone Xi R36 F R11 R66-67	10-12.5%
	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane F+ R12	5-10%
	Flam. Gas 1, H220 Press. Gas C, H280	



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon/produktion.de  
 http://www.chamaeleon/produktion.de

CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-XXXX	isobutane F+ R12	5-10%
	Flam. Gas 1, H220 Press. Gas C, H280	
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35-XXXX	Solvent naphtha (petroleum), light arom. (< 0,1 % benzol CAS nr. 71-43-2) Xn R65 Xi R37 N R51/53 R10-66-67 Carc. Cat. 2, Muta. Cat. 2	1-2.5%
	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336	
CAS: 67-56-1 EINECS: 200-659-6 Index number: 603-001-00-X Reg.nr.: 01-2119433307-44-XXXX	methanol T R23/24/25-39/23/24/25 F R11	0.1-1%
	Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370	

**Additional information:** For the wording of the listed risk phrases refer to section 16.

#### 4- FIRST - AID MEASURE

##### **Description of first aid measures**

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Generally the product does not irritate the skin.

**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

**Most important symptoms and effects, both acute and delayed** No further relevant information available.

#### 5- FIRE - FIGHTING MEASURE

##### **Extinguishing media**

**Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon/produktion.de  
http://www.chamaeleon/produktion.de

**For safety reasons unsuitable extinguishing agents:** Water with full jet  
**Special hazards arising from the substance or mixture** No further relevant information available.

**Advice for firefighters -**

**Protective equipment:** No special measures required.

## **6- ACCIDENTAL RELEASE MEASURE**

### **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources.

#### **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:** Ensure adequate ventilation.

#### **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **7- HANDLING AND STORAGE**

**Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

#### **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

#### **Conditions for safe storage, including any incompatibilities**

##### **Storage:**

##### **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** Protect from heat and direct sunlight.

**Specific end use(s)** No further relevant information available.



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon/produktion.de  
 http://www.chamaeleon/produktion.de

## 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

**Additional information about design of technical facilities:** No further data; see item 7.

### **Control parameters**

<b>Ingredients with limit values that require monitoring at the workplace:</b>	
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
106-97-8 butane	
WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
67-56-1 methanol	
WEL	Short-term value: 333 mg/m <sup>3</sup> , 250 ppm Long-term value: 266 mg/m <sup>3</sup> , 200 ppm Sk

**Additional information:** The lists valid during the making were used as basis.

### **Exposure controls**

#### **Personal protective equipment:**

#### **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

**Respiratory protection:** Not required.

#### **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves** Not required.

**Penetration time of glove material** Not required.

**Eye protection:** Not required.

## 9 – PHYSICAL AND CHEMICAL PROPERTIES

<b>Information on basic physical and chemical properties</b>	
<b>General Information</b>	
<b>Appearance:</b>	
<b>Form:</b>	<i>Aerosol</i>
<b>Colour:</b>	<i>According to product specification</i>
<b>Odour:</b>	<i>Characteristic</i>
<b>Odour threshold:</b>	<i>Not determined.</i>
<b>pH-value:</b>	<i>Not determined.</i>



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon/produktion.de  
 http://www.chamaeleon/produktion.de

<b>Change in condition</b>	
<b>Melting point/Melting range:</b>	<i>Undetermined.</i>
<b>Boiling point/Boiling range:</b>	<i>Not applicable, as aerosol</i>
<b>Flash point:</b>	<i>&lt; 0 °C (&lt; 32 °F)</i> <i>Not applicable, as aerosol</i>
<b>Flammability (solid, gaseous):</b>	<i>Not applicable.</i>
<b>Ignition temperature:</b>	<i>&gt; 200 °C (&gt; 392 °F)</i>
<b>Decomposition temperature:</b>	<i>Not determined.</i>
<b>Self-igniting:</b>	<i>Product is not selfigniting.</i>
<b>Danger of explosion:</b>	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible</i>
<b>Explosion limits:</b>	
<b>Lower:</b>	<i>0.6 Vol %</i>
<b>Upper:</b>	<i>3.0 Vol %</i>
<b>Vapour pressure at 20 °C (68 °F):</b>	<i>3500 hPa (2625 mm Hg)</i>
<b>Density at 20 °C (68 °F):</b>	<i>0.764 g/cm<sup>3</sup> (6.376 lbs/gal)</i>
<b>Relative density</b>	<i>Not determined.</i>
<b>Vapour density</b>	<i>Not determined.</i>
<b>Evaporation rate</b>	<i>Not applicable.</i>
<b>Solubility in / Miscibility with water:</b>	<i>Not miscible or difficult to mix.</i>
<b>Partition coefficient (n-octanol/water):</b>	<i>Not determined.</i>
<b>Viscosity:</b>	
<b>Dynamic:</b>	<i>Not determined.</i>
<b>Kinematic:</b>	<i>Not determined.</i>
<b>Solvent content:</b>	
<b>Organic solvents:</b>	<i>72.0 %</i>
<b>EU-VOC:</b>	<i>549.8 g/l</i>
<b>EU-VOC in %:</b>	<i>71.97 %</i>
<b>Solids content:</b>	<i>30.4 %</i>
<b>Other information</b>	<i>No further relevant information available.</i>

## 10- STABILITY AND REACTIVITY

### Reactivity

#### Chemical stability

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of hazardous reactions:** No dangerous reactions known.

**Conditions to avoid:** No further relevant information available.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:** No dangerous decomposition products known.



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon/produktion.de  
 http://www.chamaeleon/produktion.de

## 11- TOXICOLOGICAL INFORMATION

### Information on toxicological effects

#### Acute toxicity:

<b>LD/LC50 values relevant for classification:</b>		
64742-49-0 Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>193 mg/m <sup>3</sup> (rat)
64742-49-0 Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>193 mg/m <sup>3</sup> (rat)
67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	39 mg/m <sup>3</sup> (rat)
106-97-8 butane		
Inhalative	LC50 / 4 h	658000 mg/m <sup>3</sup> (rat)
64742-95-6 Solvent naphtha (petroleum), light arom. (< 0,1 % benzol CAS nr. 71-43-2)		
Oral	LD50	3592 mg/kg (rat) (OECD401)
Dermal	LD50	>3160 mg/kg (rab) (OECD402)
Inhalative	LC50 / 4 h	>6193 mg/m <sup>3</sup> (rat)
67-56-1 methanol		
Oral	LD50	5628 mg/kg (rat)
Dermal	LD50	15800 mg/kg (rabbit)

#### Primary irritant effect:

**on the skin:** No irritant effect.

**on the eye:** No irritant effect.

**Sensitization:** No sensitizing effect known.

## 12 – ECOLOGICAL INFORMATION

### Toxicity

<b>Aquatic toxicity:</b>	
64742-49-0 Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)	
LC50	127-159 mg/l (Leuciscus idus)
64742-49-0 Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)	
LC50	127-159 mg/l (Leuciscus idus)





Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon/produktion.de  
 http://www.chamaeleon/produktion.de

67-64-1 acetone	
EC50 / 48 h	8800 mg/l (daphnia magna)
LC50 / 48 h	2262 mg/l (daphnia magna)
LC50 / 96 h (static)	5540 mg/l (fish)
64742-95-6 Solvent naphtha (petroleum), light arom. (< 0,1 % benzol CAS nr. 71-43-2)	
EC50 / 24 h	150 mg/l (daphnia magna)
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	3.77 mg/l (fish)

**Persistence and degradability** No further relevant information available.

**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

**Ecotoxicological effects:**

**Remark:** Toxic for fish

**Additional ecological information:**

**General notes:**

**Water hazard class 2** (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**Other adverse effects** No further relevant information available.

### **13- DISPOSAL CONSIDERATION**

**Waste treatment methods**

**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

<b>European waste catalogue</b>	
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging
15 01 11*	metallic packaging containing a dangerous solid porous matrix(for example asbestos), including empty pressure containers

**Uncleaned packaging:**

**Recommendation:** Non contaminated packagings may be recycled.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon/produktion.de  
http://www.chamaeleon/produktion.de

## 14- TRANSPORT INFORMATION

### UN-Number

ADR, IMDG, IATA UN1950

### UN proper shipping name

ADR 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS  
IMDG AEROSOLS  
IATA AEROSOLS, flammable

### Transport hazard class(es)

ADR



Class 2 5F Gases  
Label 2.1

IMDG , IATA



Class 2.1  
Label 2.1

### Packing group

ADR, IMDG, IATA Void

### Environmental hazards:

Marine pollutant: No

### Special precautions for user

Warning: Gases.  
Danger code (Kemler): -  
EMS Number: F-D,S-U

**Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

### Transport/Additional information:

ADR

Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon/produktion.de  
http://www.chamaeleon/produktion.de

Transport category 2  
Tunnel restriction code D

#### IMDG

Limited quantities (LQ) 1L  
Excepted quantities (EQ) Code: E0  
Not permitted as Excepted Quantity  
UN "Model Regulation": UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY  
HAZARDOUS

### 15 – REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture .** No further relevant information available

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16-OTHER INFORMATION

#### Relevant phrases

H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H301 Toxic if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H370 Causes damage to organs.  
H411 Toxic to aquatic life with long lasting effects.

R10 Flammable.  
R11 Highly flammable.  
R12 Extremely flammable.  
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.  
R36 Irritating to eyes.  
R37 Irritating to respiratory system.  
R38 Irritating to skin.  
R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon/produktion.de](mailto:info@chamaeleon/produktion.de)  
<http://www.chamaeleon/produktion.de>

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness..

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.