



Chamäleon GmbH
 Rudolf-Diesel-Straße, 8a
 69115 Heidelberg-Germany
 Tel.: +49-(0)-6221 520440
 Fax: +49-(0)-6221 520449
 E-mail: info@chamaeleon/produktion.de
 http://www.chamaeleon/produktion.de

TECHNICAL DATA SHEET

ANTI-GRAVEL PREMIUM

Article number: 37215, 37225, 37235, 37315, 37325, 37335

Intended use: Car refinishing product/ Protector

General characteristics: 1K high performance HS stone chip protector.

Product characteristics: It is a ready to use product, with high coverage power and with no risk of runs. Its formulation provides a great flexibility level, what makes it perfect for anticorrosive protection and protection against impacts in parts as underbodies and wheel wells. Besides, guarantees an optimal soundproofing in applications over parts with a high level of vibrations as doors, boots, or panels. Once dry, Anti-gravel premium presents an excellent texture or orange peel effect, what allows it to be over-painted with bodywork basecoat paints, achieving a perfect gloss level.

Physical and chemical characteristics:

Nature:	Synthetic resins
Colour:	Light grey, dark grey, black, white
Specific weight:	1,5 kg/l at 20°C
Dry film thickness:	150-200 microns 1 coat
Yield:	5-7 m ² /Kg
VOC:	410 g/l
Solid content:	72 %

Application:




Method of application

Shake before using	RB1 schutz gun	3-4 kg/cm ²	15-25	1-2
	HP cannister gun	2 kg/cm ²		



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
<http://www.chamaeleon/produktion.de>

Drying times:

		
10°C	2h	90'
20°C	1,5h	60'
30°C	1h	45'

Remarks:

- The product is ready to use and it does not require additional thinner.
- Shake before using.
- Apply to grease and rust-free surfaces.
- Avoid any mechanical action against the treated parts before 24 hours (for example: car wash with high pressure hot water).
- The product can be over-painted at 30' - 40', only if the paint is dried at ambient temperature.

Equipment cleaning:

Clean the equipment with a cleaning thinner before the pot life has expired.

Safety:

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

Storage:

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

Guarantee:

In unopened original packaging, one year from manufacturing date.

Data: 14, October 2014

This release replaces all eventually earlier issued versions.

***For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: info@chamaeleon-produktion.de
See information on safety in Safety Data Sheet.***