



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
http://www.chamaeleon/produktion.de

TECHNICAL DATA SHEET

GLASS PRIMER

Article number: 38721

Intended use: Car refinishing Product/ Adhesion promoter

General characteristics: Glass Primer is a black primer specifically designed for the ceramic band on vehicle glass. It ensures the complete protection of the adhesive by crating a barrier against harmful UV rays which can lead to the degradation of the adhesive. It is also an adhesion promoter..

Product characteristics: Glass Primer improves sealant adhesion on glass, ceramic coated glass and on different plastic and metal materials.

Technical Characteristics:

Appearance	Liquid free from lumps
Colour	Black
Chemical nature	Polyisocyanates
Curing Mechanism	Moisture-curing
Density [g/cc]	1,03 ± 0,02
Drying time [min] (23°C and 50%)	10
Application	Felt applicator
Application temperature [°C]	From +10 to +35

Application:

The surfaces to be treated must be perfectly clean, dry, dust and grease free. Application of Glass Primer can only take place once the thorough cleaning of the bonding area with Activator has been completed. Shake bottle well before application (for at least 1 min.) till noise of the metal balls contained in the bottle can be heard. Close immediately after use as product evaporates very quickly. Ensure that primer is tack-free dry before proceeding. An open time of longer than 24 hours necessitates reactivating the primer.

Coverage:

Glass Primer has consumption of about 150g/m².



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
<http://www.chamaeleon/produktion.de>

Personal protective measures:

Avoid skin contact using latex, rubber or polyethylene gloves.

Packing: Drum 200 Lt (206 kg)

Storage:

Glass Primer can be stored for 12 months in its original packing at 10°-25°C.

The product is flammable. Keep away from heat sources, store in a dry and well-ventilated area in its original packaging.

Keep out of the reach of children.

ALWAYS CONSULT THE SAFETY DATA SHEETS BEFORE USING THE PRODUCT

Data: 09, November 2014

This release replaces all eventually earlier issued versions.

For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: info@chamaeleon-produktion.de

See information on safety in Safety Data Sheet.