



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleonproduktion.de](mailto:info@chamaeleonproduktion.de)  
<http://www.chamaeleonproduktion.de>

## *TECHNICAL DATA SHEET*

### CHAMÄLEON MASKING TAPE

<b>Article number:</b>	<b>48111; 48121, 48141, 48151</b>
<b>Intended use:</b>	Masking the car body when refinishing
<b>Technical characteristics:</b>	
<b>Heat resistant:</b>	80°C
<b>Wides:</b>	19mm*45m, 25mm*45m, 38mm*45m, 50mm*45m
<b><u>Film properties:</u></b>	
<b>Type of Film:</b>	Impregnated Crepe Paper
<b>Film Thickness:</b>	90 ± 15 µm
<b>Tensile Strength MD:</b>	50 ± 15 N/mm <sup>2</sup>
<b>Elongation at Break MD:</b>	9 ± 2%
<b><u>Adhesive properties:</u></b>	
<b>Type of Adhesive:</b>	Solvent-based, Natural Rubber
<b>Colour:</b>	Light beige
<b>Peel Adhesion:</b>	4.0 ± 1 N/25mm
<b>Rolling Ball Tack:</b>	under 3 cm
<b>Prior to use:</b>	Carefully check that the contact surfaces are totally dry and clean from oil, grease and dust.
<b>Storage conditions:</b>	around 21 °C and 50% relative humidity.

The data stated above cannot be considered as binding by contract or by specifications. They correspond to the average values obtained from the tests carried out according to Atlas Tapes norms, in conformity with AFERA norms. Tests are carried out on samples taken from our standard production. These data may vary without any notice – the updated typical value sheets can be forwarded at any time. Since many different factors may influence the product's performance, we recommend testing the product by any application. We remain at your disposal for any further information or recommendations.

*For the additional information that is not included to the Technical Data Sheet apply to the supplier:  
e-mail: [info@chamaeleonproduktion.de](mailto:info@chamaeleonproduktion.de)  
See information on safety in Safety Data Sheet.*