



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
http://www.chamaeleon/produktion.de

TECHNICAL DATA SHEET

SOFT EDGE FOAM MASKING TAPE

Article number: 48351 (20m)

Intended use: Masking, Filling

General characteristics:

- filling any spaces between the doors, bonnet, boot lid and the body of the vehicle,
- produces the required soft paint edge; masking the borders of painting elements to avoid rework due to unwanted „tape line“.

Product characteristics:

- colour white,
- excellent flexibility,
- vibration and noise damping,
- resistance to impact and temperature,
- good insulation properties.

Usage: Stick the foam strip at the ordered varnish transition or in a seal place in the car aperture.
Sticks perfectly to the uneven surface.
Foam stripes are easy to separate.

Technical characteristics:

Composition: elastic polyurethane (PU) ester foam tape, made of a free-foaming method, VOC free (volatile organic compounds), layer of glue, protective layer,

Physical parameters:

Parameter	Unit	Value
Density	kg/m ³	24-27
Rigidity 50%	hPa	75 +/-15
Permanent deformation	%	<60
Tensile Strength	hPa	>700
Elongation at break	%	>100
Resistance to aging	%	>40
Cells density	pcs/cm ²	19 +/-3



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
<http://www.chamaeleon/produktion.de>

Available sizes:

13mm x 20m,
13mm x 50m.

Data: 23, December 2013

This release replaces all eventually earlier issued versions.

*For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: info@chamaeleon-produktion.de
See information on safety in Safety Data Sheet.*