



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

***SAFETY DATA SHEET***  
***according to 1907/2006/EC, Article 31***      *Revision date: 25.11.2015*

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**

**Product details**

**Trade name:** 1K Acrylic Lacquer Black Matt

**Article number:** 50010

**Intended use:** Car refinishing Product/ Lacquer

**Manufacturer/Supplier:** Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg -- Germany

**Further information obtainable from:** Product Safety Department

**Information in case of emergency:** + 49 70024112112 (CH)

**2 – HAZARDS IDENTIFICATION**

**Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3    H226 Flammable liquid and vapour.



GHS07

Eye Irrit. 2    H319 Causes serious eye irritation.

STOT SE 3    H336 May cause drowsiness or dizziness.

**Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

R10-66-67:      Flammable. Repeated exposure may cause skin dryness or cracking.  
                         Vapours may cause drowsiness and dizziness.

**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Has a narcotizing effect.

**Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

## Label elements

### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

### Hazard pictograms



GHS02      GHS07

**Signal word:** Warning

### Hazard-determining components of labelling:

n-butyl acetate

Solvent naphtha (petroleum), light arom.

isobutanol

### Hazard statements:

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

### Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

### Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http://www.chamaeleon-produktion.de

### **3– COMPOSITION/INFORMATION ON INGREDIENTS**

#### **Chemical characterization: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

<b>Dangerous components:</b>		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.:01-2119485493-29	n-butyl acetate R10-66-67	25-50%
	Flam. Liq. 3, H226; STOT SE 3, H336	
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Xn R65; Xi R37; N R51/53 R10-66-67	0.1-<2.5%
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	
CAS: 78-83-1 EINECS: 201-148-0 Reg.nr.:01-2119484609-23	isobutanol Xi R37/38-41 R10-67	1-<2.5%
	Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 1333-86-4 EINECS: 215-609-9 Reg.nr.: 01-2119384822-32	Carbon black substance with a Community workplace exposure limit	0.1-<2.5%

**Additional information:** For the wording of the listed risk phrases refer to section 16.

### **4– FIRST - AID MEASURE**

#### **Description of first aid measures**

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:** If symptoms persist consult doctor.

#### **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

#### **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### **5– FIRE - FIGHTING MEASURE**

#### **Extinguishing media**

Suitable extinguishing agents: CO<sub>2</sub>, sand, extinguishing powder. Do not use water.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**Special hazards arising from the substance or mixture**

No further relevant information available.

**Advice for firefighters**

Protective equipment: No special measures required.

## **6– ACCIDENTAL RELEASE MEASURE**

**Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **7– HANDLING AND STORAGE**

**Precautions for safe handling** No special precautions are necessary if used correctly.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** No special requirements.

**Information about storage in one common storage facility:** Store away from foodstuffs.

**Further information about storage conditions:** Keep container tightly sealed.

**Storage class:** 3

**Specific end use(s)** No further relevant information available.

## **8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Additional information about design of technical facilities:** No further data; see item 7.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

### Control parameters

Ingredients with limit values that require monitoring at the workplace:	
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
78-83-1 isobutanol	
WEL	Short-term value: 231 mg/m <sup>3</sup> , 75 ppm Long-term value: 154 mg/m <sup>3</sup> , 50 ppm
1333-86-4 Carbon black	
WEL	Short-term value: 7 mg/m <sup>3</sup> Long-term value: 3.5 mg/m <sup>3</sup>

**Additional information:** The lists valid during the making were used as basis.

### Exposure controls

#### Personal protective equipment:

**General protective and hygienic measures:** Wash hands before breaks and at the end of work.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** Tightly sealed goggles

## 9 – PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

#### General Information

##### Appearance:

##### Form:

*Fluid*

##### Colour:

*According to product specification*

##### Odour:

*Characteristic*

##### Odour threshold:

*Not determined.*



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon-produktion.de  
 http: //www.chamaeleon-produktion.de

<b>pH-value:</b>	<i>Not determined.</i>
<b>Change in condition</b>	
<b>Melting point/Melting range:</b>	<i>Undetermined.</i>
<b>Boiling point/Boiling range:</b>	<i>124°C</i>
<b>Flash point:</b>	<i>23 °C (DIN EN ISO 1523:2002)</i>
<b>Flammability (solid, gaseous):</b>	<i>Not applicable.</i>
<b>Ignition temperature:</b>	<i>370 °C (DIN 51794)</i>
<b>Decomposition temperature:</b>	<i>Not determined.</i>
<b>Self-igniting:</b>	<i>Product is not selfigniting.</i>
<b>Danger of explosion:</b>	<i>Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.</i>
<b>Explosion limits:</b>	
<b>Lower:</b>	<i>1.2 Vol %</i>
<b>Upper:</b>	<i>7.5 Vol %</i>
<b>Vapour pressure at 20°C:</b>	<i>10.7 hPa</i>
<b>Density at 20 °C:</b>	<i>0.992 g/cm<sup>3</sup> (DIN EN ISO 2811-1)</i>
<b>Relative density</b>	<i>Not determined.</i>
<b>Vapour density</b>	<i>Not determined.</i>
<b>Evaporation rate</b>	<i>Not determined.</i>
<b>Solubility in / Miscibility with water:</b>	<i>Not miscible or difficult to mix.</i>
<b>Partition coefficient (n-octanol/water):</b>	<i>Not determined.</i>
<b>Viscosity:</b>	
<b>Dynamic:</b>	<i>Not determined.</i>
<b>Kinematic at 20 °C:</b>	<i>130 s (DIN 53211/4)</i>
<b>Solvent content:</b>	
<b>VOC (EC)</b>	<i>54.15 %</i>
<b>Solids content (weight-%):</b>	<i>46.0 %</i>
<b>Other information</b>	<i>No further relevant information available.</i>

## **10– STABILITY AND REACTIVITY**

**Reactivity** No further relevant information available.

### **Chemical stability**

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of hazardous reactions:** No dangerous reactions known.

**Conditions to avoid:** No further relevant information available.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:** Carbon monoxide.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

## **11- TOXICOLOGICAL INFORMATION**

Information on toxicological effects

### **Acute toxicity:**

<b>LD/LC50 values relevant for classification:</b>		
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rab)

### **Primary irritant effect:**

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

### **Serious eye damage/irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

### **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

### **STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## **12 – ECOLOGICAL INFORMATION**

### **Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Persistence and degradability** No further relevant information available.

**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

### **Additional ecological information:**

#### **General notes:**

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### **Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**Other adverse effects** No further relevant information available.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

### **13– DISPOSAL CONSIDERATION**

#### **Waste treatment methods**

##### **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

##### **Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

### **14– TRANSPORT INFORMATION**

#### **UN-Number**

ADR, IMDG, I AT A

UN 1263

#### **UN proper shipping name**

ADR

1263 PAINT, special provision 640E

IMDG, IATA

PAINT

#### **Transport hazard class(es)**

ADR



Class

3 (F1) Flammable liquids.

Label

3

IMDG, I ATA



Class

3 Flammable liquids.

Label

3

#### **Packing group**

ADR, IMDG, I AT A

III

#### **Environmental hazards:**

Marine pollutant:

No



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

**Special precautions for**

Danger code (Kemler):

EMS Number:

Warning: Flammable liquids.

30

F-E,S-E

**Transport in bulk according to Annex II of  
MARPOL and the IBC Code** Not applicable.

**Transport/Additional information:**

**ADR**

Transport category

3

Tunnel restriction code

D/E

Remarks:

≤ 450 l: -

**IMDG**

Limited quantities (LQ)

5L

Remarks:

≤ 30 l: -

**UN "Model Regulation":**

UN 1263 PAINT, SPECIAL PROVISION 640E, 3, III, (D/E)

**15 – REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**National regulations:**

Class	Share in %
NK	50-100

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16-OTHER INFORMATION**

**Relevant phrases**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

- R10 Flammable.
- R37 Irritating to respiratory system.
- R37/38 Irritating to respiratory system and skin.
- R41 Risk of serious damage to eyes.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.