



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

## TECHNICAL DATA SHEET (Provisional)

# LASER Perfect Shine Liquid Glaze

### Product Description

LASER Perfect Shine has been developed as a high gloss finishing glaze applied by either hand or machine for use on all paint systems (fresh – well cured). Perfect Shine has a very light cutting effect.

### Product Information

| Size   | Product Code | Carton Quantity |
|--------|--------------|-----------------|
| 500 ml | 49903        | 12 pcs          |

### Applications

Use with foam or by hand application

### Characteristics

- Water based
- High gloss
- Silicone free
- Recommended with foam or hand application.
- Ready to use.
- Dry use

### Physical Properties

|                  |              |
|------------------|--------------|
| State            | Liquid       |
| Colour           | Blue         |
| Relative Density | 1.05         |
| Viscosity        | 23,000cps    |
| Flash Point      | >93°C        |
| pH               | 7-8          |
| VOC Content g/l  | Refer to SDS |

*For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
See information on safety in Safety Data Sheet.*



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

## Storage & Handling

Store at room temperature  
Protect from frost  
Shake container prior to use

## Directions For Use

*For use by hand application only:*

1. Shake the bottle and apply a small amount to a clean Finishing Cloth.
2. Using light pressure apply the glaze to the panel using a circular overlapping action to ensure even coverage.
3. Buff the surface to a durable high gloss finish using a Finishing Cloth.

*For use by machine application only:*

1. Attach the Polishing Foam to a polishing machine and set to a free running speed of 1000-1500 rpm.
2. Apply a small amount of Perfect Shine to the paint surface and spread uniformly over the surface using the Polishing Foam before starting the machine to reduce splatter
3. Run lightly over the polishing area with the Polishing Foam kept flat until the desired gloss level has been achieved.
4. Remove any residue with a Finishing Cloth.

## Additional Information

Professional users may refer to the Safety Data Sheet for this product

*For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
See information on safety in Safety Data Sheet.*