



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon/produktion.de](mailto:info@chamaeleon/produktion.de)  
<http://www.chamaeleon/produktion.de>

## *TECHNICAL DATA SHEET*

### **PENETRATING OIL**

**Article number:** 27007

**Intended use:** Car refinishing product/ Screw loosening agent

**General characteristics:** High quality effective tool to loosen rusted parts.

**Product characteristics:**

- Good penetrating properties
- Contains graphite and MoS<sub>2</sub>
- Moisture repellent
- Corrosion preventive
- Powerful jetspray
- 360° valve

**Applications:**

- Fastenings Tools
- Screwed connections Rails
- Gear wheels Chains
- Locks Garden tools
- Fasteners (screws, bolts and nuts) Reels

**Physical and Chemical Characteristics:**

Contents	: 400 ml
Basis	: Mineral Oil and graphite and MoS <sub>2</sub>
VOC-content	: Approximately 70% w/w
Colour	: Graphite / Black
Scent	: Characteristic
Relative density at 20°C	: 0,86 g/ml
Yield	: 2,33 g/sec
Vapour pressure at 20°C	: 3 to 4 bar

**Usage:**

Before use, carefully read the directions on the packaging and act accordingly. The aerosol should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol. Apply penetrating oil and allow it to take effect.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon/produktion.de](mailto:info@chamaeleon/produktion.de)  
<http://www.chamaeleon/produktion.de>

*Data: 05, October 2014*

*This release replaces all eventually earlier issued versions.*

*For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)*

*See information on safety in Safety Data Sheet.*