

Chamäleon GmbH Rudolf-Diesel-Straße, 8a 69115 Heidelberg-Germany Tel.: +49-(0)-6221 520440 Fax: +49-(0)-6221 520449 E-mail: info@chamaeleon/produktion.de http: //www. chamaeleon/produktion.de

TECHNICAL DATA SHEET

MULTI SPRAY

27009

Intended use:

General characteristics:

Product characteristics:

Car refinishing Product/ Lubricant

High quality universal oil to lubricate, protect and clean parts of metal and plastic.

- Good penetrating properties
- Moisture repellent
- Removes oil, grease, wax, underbody coating and tar
- Cleansing effect
- Corrosion preventive
- Directed jetspray
- After cleaning, a protective film remains

Applications:

Chains liable to light load	Fastenings
Locks	Tools
Garden Tools	Machinery
Fasteners (screws, bolts and nuts)	Motions
Pedals Hometrainer	
Skeelers, Skates, Skateboards	

Physical and Chemical Characteristics:

Contents	: 400 ml
Basis	: Mineral Oil
VOC-content	: Approximately 82% w/w
Colour	: Transparent light brown
Scent	: Vanilla
Relative density at 20°C	: 0,80 g/ml
Yield	: 1,98 g/sec
Vapour pressure at 20°C	: 3 to 4 bar
Temperature resistant	: -50°C to +200 °C



Chamäleon GmbH Rudolf-Diesel-Straße, 8a 69115 Heidelberg-Germany Tel.: +49-(0)-6221 520440 Fax: +49-(0)-6221 520449 E-mail: info@chamaeleon/produktion.de http: //www. chamaeleon/produktion.de

Usage:

Before use, carefully read the directions on the packaging and act accordingly. The aerosol should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol. Apply multispray in the desired quantity. The optimum lubrication is obtained after evaporation of the solvent.

Data: 05, October 2014 This release replaces all eventually earlier issued versions.

For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: <u>info@chamaeleon-produktion.de</u> See information on safety in Safety Data Sheet.