



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon-produktion.de
<http://www.chamaeleon-produktion.de>

TECHNICAL DATA SHEET

FINE LINE TAPE

Article number: 48360, 48361

Intended use: Car refinishing product/ Masking

General characteristics: Fine Line Tape is a high temperature fine line tape which adheres excellent to a wide variety of surfaces. This tape will perform in the presence of 150°C temperature for at least one hour. It follows contours and remains in place as long as necessary. Leaves no residue upon removal.

Construction:

Adhesive	Rubber
Carrier	Plasticized PVC film
	Dark blue

Applications:

Car:

- Multi-colour paint applications
- Aftermarket autobody
- Fine line masking tape
- Plastic parts (bumpers)

Industry:

- Multi-colour paint applications
- Not recommended for outdoor use

Technical characteristics:

Total thickness	0,16 mm
Adhesive strength	6,5 N/25 mm
Tensile strength	77,5 N/25 mm
Elongation	130%
Maximum temperature	+150°C
Solvent resistance	Very good



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon-produktion.de
<http://www.chamaeleon-produktion.de>

Recommendations for use:

Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

Storage:

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C.

Data: 5, April 2016

This release replaces all eventually earlier issued versions.

*For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: info@chamaeleon-produktion.de
See information on safety in Safety Data Sheet.*