



Chamäleon GmbH  
 Rudolf-Diesel-Straße, 8a  
 69115 Heidelberg-Germany  
 Tel.: +49-(0)-6221 520440  
 Fax: +49-(0)-6221 520449  
 E-mail: info@chamaeleon/produktion.de  
 http://www.chamaeleon/produktion.de

**TECHNICAL DATA SHEET**

"

**NQPI 'NKHG'RQNKUJ KPI 'RCF'/'J CTF '\*Qt cpi g+'**

**Ct vleg'pwo dgt<** 49871  
"

**Kvqpf gf 'wug<'"** Car refinishing product/ Polishing, griding

**I gpgt cněj ct cevgt kuleu<'"**

- Áfor mechanical polishing and griding;
- Ásuited for using with coarse-grained polishing pastes.

**Rt qf wev'ej ct cevgt kuleu<**

- Ástructure of the foam allow to hold the water inside the pad, what decrease the temperature of the polishing surface;
- Áthe pad does not get into vibration during the work, which has a considerable effect on its life time;
- Áthe Velcro holder is made from very strong, reusable material. It allows the pad to be securaly fitted into the polisher;

▪Á color: Orange

**Cxckrdg'v' r gu'qhy qt npi 'wt hreg<'"**

▪Áflat

"

**Vgej pkecnej ct cevgt kuleu<**

- Áthe Velcro holder hook-up type
- Áthe foam is polyurethane, polyester type, high resistantce and shock absorption
- Ágenera physical parameters of foam:

FEATURES	UNIT	VALUE
Density	kg/m3	32 – 38



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon/produktion.de](mailto:info@chamaeleon/produktion.de)  
<http://www.chamaeleon/produktion.de>

Rigidity 40%	kPa	6,0 – 8,5
Elongation at break	%	170
Tensile strenght	kPa	180
Cell diameter	Mikron	480 – 660
Max compression set	%	6,7

### Usage:

the pad can be applied both wet and dry at maximum rotation speed 2600 rpm without load.

### Available sizes:

150mm x 25mm

### Available holders:

Velcro

*Data: 19, April 2018*

*This release replaces all eventually earlier issued versions.*

*For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)*

*See information on safety in Safety Data Sheet.*