



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

## *TECHNICAL DATA SHEET*

### CHAMÄLEON MASKING TAPE

<b>Article number:</b>	<b>48112; 48122, 48142, 48152</b>
<b>Intended use:</b>	Masking the car body when refinishing
<b>Technical characteristics:</b>	
<b>Heat resistant::</b>	60°C / 60min
<b>Wides:</b>	18mm*50m, 24mm*50m, 36mm*50m, 48mm*50m
<b><u>Film properties:</u></b>	
<b>Type of Film:</b>	Impregnated Crepe Paper
<b>Film Thickness:</b>	120 µm
<b>MD tensile strength:</b>	38 N/cm
<b>Elongation at Break MD:</b>	Min 7 %
<b><u>Adhesive properties:</u></b>	
<b>Type of Adhesive:</b>	Solvent-borne, rubber resin
<b>Colour:</b>	Beige
<b>Adhesion to steel plate:</b>	2.1 N/cm
<b>Prior to use:</b>	Carefully check that the contact surfaces are totally dry and clean from oil, grease and dust.
<b>Storage conditions:</b>	around 21 °C and 50% relative humidity.

*For the additional information that is not included to the Technical Data Sheet apply to the supplier:  
e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
See information on safety in Safety Data Sheet.*