



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon-produktion.de
<http://www.chamaeleon-produktion.de>

TECHNICAL DATA SHEET

CHAMÄLEON MASKING TAPE

Article number:	48212; 48222, 48242, 48252
Intended use:	Masking the car body when refinishing
Technical characteristics:	
Heat resistant::	90°C / 60min
Wides:	18mm*50m, 24mm*50m, 36mm*50m, 48mm*50m
<u>Film properties:</u>	
Type of Film:	Impregnated Crepe Paper
Film Thickness:	125 µm
MD tensile strength:	38 N/cm
Elongation at Break MD:	Min 7 %
<u>Adhesive properties:</u>	
Type of Adhesive:	Solvent-borne, rubber resin
Colour:	Brown
Adhesion to steel plate:	2.3 N/cm
Prior to use:	Carefully check that the contact surfaces are totally dry and clean from oil, grease and dust.
Storage conditions:	around 21 °C and 50% relative humidity.

*For the additional information that is not included to the Technical Data Sheet apply to the supplier:
e-mail: info@chamaeleon-produktion.de
See information on safety in Safety Data Sheet.*