

***SAFETY DATA SHEET***  
***according to 1907/2006/EC, Article 31***    *Revision date: 17/09/2015*

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**

**Product details**

**Trade name:** HS Hardener LOW VOC Fast

**Article number:** 12274, 12277

**Intended use:** Car refinishing Product/ Hardening agent/ Curing agent

**Manufacturer/Supplier:** Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg -- Germany

**Further information obtainable from:** Product Safety Department

**Information in case of emergency:** + 49 70024112112 (CH)

**2 – HAZARDS IDENTIFICATION**

**Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

**Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xn; Harmful

R20: Harmful by inhalation.

Xi; Irritant

R37: Irritating to respiratory system.

Xi; Sensitising

R43: May cause sensitisation by skin contact.

R10-66: Flammable. Repeated exposure may cause skin dryness or cracking.

**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

**Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

**Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS02

GHS07

**Signal word** Warning**Hazard-determining components of labelling:**

Hexamethylene diisocyanate, oligomers

n-butyl acetate

2-ethoxy-1-methylethyl acetate

4-isocyanatosulphonyltoluene

dibutyltin dilaurate

**Hazard statements**

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

Restricted to professional users.

**Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

### **3- COMPOSITION/INFORMATION ON INGREDIENTS**

#### **Chemical characterization: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

<b>Dangerous components:</b>		
CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17 01-2119488934-20	Hexamethylene diisocyanate, oligomers Xn R20; Xi R37; Xi R43	50-100%
	Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate R10-66-67	25-50%
	Flam. Liq. 3, H226; STOT SE 3, H336	
CAS: 54839-24-6 EINECS: 259-370-9 Reg.nr.: 01-2119475116-39	2-ethoxy-1-methylethyl acetate R10-67	15-<25%
	Flam. Liq. 3, H226; STOT SE 3, H336	
CAS: 77-58-7 EINECS: 201-039-8 Reg.nr.: 01-2119496068-27	dibutyltin dilaurate T R60-61-48/25; C R34; Xn R68; Xi R43; N R50/53	0.1-<0.25%
	Muta. 2, H341; Repr. 1B, H360Fd; STOT RE 1, H372; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	
CAS: 4083-64-1 EINECS: 223-810-8	4-isocyanatosulphonyltoluene Xi R36/37/38; Xn R42 R14	0.1-<1%
	Resp. Sens. 1, H334; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	

**Additional information:** For the wording of the listed risk phrases refer to section 16.

### **4- FIRST - AID MEASURE**

#### **Description of first aid measures**

##### **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

##### **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:** If symptoms persist consult doctor.

**Most important symptoms and effects, both acute and delayed** No further relevant information available.

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available

## **5- FIRE - FIGHTING MEASURE**

### **Extinguishing media**

**Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

### **Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

Hydrogen cyanide (HCN)

### **Advice for firefighters**

**Protective equipment:** Mouth respiratory protective device.

## **6- ACCIDENTAL RELEASE MEASURE**

### **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

### **Environmental precautions:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Contain and collect spillages with non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth) and place in a suitable container.

Decontaminate immediately with suitable mixture (flammable):

- as such usable (inflammatory!):

water 45 Vol.%

ethanol or isopropanol 50 Vol.%

ammonia solution (Density= 0.88) 5 Vol.%

- alternatively (non-flammable):

sodium carbonate 5 Vol.%

water 95 Vol.%

Add the same decontaminant to any residues and allow to stand for several days in a non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of in accordance with the waste regulations (see Section 13).

**Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**7- HANDLING AND STORAGE**

**Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

Persons with a history of asthma, allergies or chronic or recurrent respiratory diseases should only be employed in processes in which this product is used under appropriate medical supervision.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** No special requirements.

**Information about storage in one common storage facility:**

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.  
Store away from foodstuffs.

**Further information about storage conditions:**

Keep container tightly sealed.  
Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohol and water.

**Storage class:** 3

**Specific end use(s)** No further relevant information available.

**8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Additional information about design of technical facilities:** No further data; see item 7.

**Control parameters**

<b>Ingredients with limit values that require monitoring at the workplace:</b>	
28182-81-2 Hexamethylene diisocyanate, oligomers	
EBW	Short-term value: 0.5 mg/m <sup>3</sup> exposition evaluation valu TRGS 430 (EBW)
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm

77-58-7 dibutyltin dilaurate	
WEL	Short-term value: 0.2 mg/m <sup>3</sup> Long-term value: 0.1 mg/m <sup>3</sup> as Sn; Sk

**Additional information:** The lists valid during the making were used as basis.

**Exposure controls**

**Personal protective equipment:**

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

**General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.

**Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
Filter A/P2 (EN 141, EN 143)

**Protection of hands:**

Protective gloves (EN 374)

**Material of gloves**

- Butyl rubber, BR
- Recommended thickness of the material:  $\geq 0.7$  mm.

**Penetration time of glove material** Value for the permeation: Level  $\leq 3$

**Eye protection:** Tightly sealed goggles

**9 – PHYSICAL AND CHEMICAL PROPERTIES**

<b>Information on basic physical and chemical properties</b>	
<b>General Information</b>	
<b>Appearance:</b>	
<b>Form:</b>	<i>Fluid</i>
<b>Colour:</b>	<i>According to product specification</i>
<b>Odour:</b>	<i>Characteristic</i>
<b>Odour threshold:</b>	<i>Not determined.</i>
<b>pH-value:</b>	<i>Not determined.</i>
<b>Change in condition</b>	
<b>Melting point/Melting range:</b>	<i>Undetermined.</i>
<b>Boiling point/Boiling range:</b>	<i>124 °C</i>
<b>Flash point:</b>	<i>28 °C (DIN 53213)</i>
<b>Flammability (solid, gaseous):</b>	<i>Not applicable.</i>
<b>Ignition temperature:</b>	<i>370 °C (DIN 51794)</i>

<b>Decomposition temperature:</b>	<i>Not determined.</i>
<b>Self-igniting:</b>	<i>Product is not selfigniting.</i>
<b>Danger of explosion:</b>	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible..</i>
<b>Explosion limits:</b>	
<b>Lower:</b>	<i>1.2 Vol %</i>
<b>Upper:</b>	<i>7.5 Vol %</i>
<b>Vapour pressure at 20 °C:</b>	<i>10.7 hPa</i>
<b>Density at 20 °C:</b>	<i>1.03 g/cm<sup>3</sup> (DIN 53217)</i>
<b>Relative density</b>	<i>Not determined.</i>
<b>Vapour density</b>	<i>Not determined.</i>
<b>Evaporation rate</b>	<i>Not determined.</i>
<b>Solubility in / Miscibility with water:</b>	<i>Not miscible or difficult to mix.</i>
<b>Partition coefficient (n-octanol/water):</b>	<i>Not determined.</i>
<b>Viscosity:</b>	
<b>Dynamic:</b>	<i>Not determined.</i>
<b>Kinematic at 20 °C:</b>	<i>13 s (DIN 53211/4)</i>
<b>Solvent content:</b>	
<b>VOC- (EC)</b>	<i>45.42 %</i>
<b>Solids content (weight-%):</b>	<i>54.5 %</i>
<b>Other information</b>	<i>No further relevant information available.</i>

## 10– STABILITY AND REACTIVITY

### Reactivity

#### Chemical stability

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of hazardous reactions** No dangerous reactions known.

**Conditions to avoid** No further relevant information available.

**Incompatible materials:** No further relevant information available.

#### **Hazardous decomposition products:**

Possible in traces.

Nitrogen oxides

Hydrogen chloride (HCl)

Hydrogen cyanide (prussic acid)

Carbon monoxide

Nitrogen oxides (NOx)

## **11- TOXICOLOGICAL INFORMATION**

### **Information on toxicological effects**

#### **Acute toxicity:**

#### **Primary irritant effect:**

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation** Based on available data, the classification criteria are not met.

#### **Respiratory or skin sensitisation**

May cause an allergic skin reaction.

#### **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause respiratory irritation. May cause drowsiness or dizziness.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## **12 – ECOLOGICAL INFORMATION**

### **Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Persistence and degradability** No further relevant information available.

**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

#### **Additional ecological information:**

##### **General notes:**

**Water hazard class 1 (German Regulation) :** slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### **Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**Other adverse effects** No further relevant information available.

## **13– DISPOSAL CONSIDERATION**

### **Waste treatment methods**

#### **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.



<b>European waste catalogue</b>	
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**14- TRANSPORT INFORMATION**

**UN-Number**

ADR, IMDG, IATA

UN1263

**UN proper shipping name**

ADR

1263 PAINT RELATED MATERIAL , special provision  
640E

IMDG, IATA

PAINT RELATED MATERIAL

**Transport hazard class(es)**

ADR



Class  
Label

3 (F1) Flammable liquids.  
3

IMDG, IATA



Class  
Label

3 Flammable liquids.  
3

**Packing group**

ADR, IMDG, IATA

III

**Environmental hazards:**

Marine pollutant:

No

**Special precautions for user** Warning: Flammable liquids.  
**Danger code (Kemler):** 30  
**EMS Number:** F-E,S-E

**Transport in bulk according to Annex II of MARPOL and the IBC Code** Not applicable.

**Transport/Additional information:**

**ADR**  
**Transport category** 3  
**Tunnel restriction code** D/E

**IMDG**  
**Limited quantities (LQ)** 5L

**UN "Model Regulation":** UN 1263 PAINT RELATED MATERIAL, SPECIAL PROVISION 640E, 3, III, (D/E)

**15 – REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture.**

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category P5c** FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**National regulations:**

Class	Share in %
I	0.1-<1
NK	25-50

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16-OTHER INFORMATION**

**Relevant phrases**

- H226 Flammable liquid and vapour.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H360Fd May damage fertility. Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

R10 Flammable.

R14 Reacts violently with water.

R20 Harmful by inhalation.

R34 Causes burns.

R36/37/38 Irritating to eyes, respiratory system and skin.

R37 Irritating to respiratory system.

R42 May cause sensitisation by inhalation.

R43 May cause sensitisation by skin contact.

R48/25 Toxic: danger of serious damage to health by prolonged exposure if swallowed.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R60 May impair fertility.

R61 May cause harm to the unborn child.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

R68 Possible risk of irreversible effects.

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



CHAMÁLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÁLEON GMBH  
RUDOLF-DIESEL-STRASSE 8A  
69115 HEIDELBERG  
GERMANY

FON 0049 (0) 6221 - 520 440  
FAX 0049 (0) 6221 - 520 449  
MAIL [INFO@CHAMAELEON-PRODUKTION.DE](mailto:INFO@CHAMAELEON-PRODUKTION.DE)  
WEB [WWW.CHAMAELEON-PRODUKTION.DE](http://WWW.CHAMAELEON-PRODUKTION.DE)